## NSN 5305-00-722-4710

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-722-4710

| Thread Class:  |
|--|
| 2a   |
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| Between 1.179 inches and 1.250 inches  |
| Fastener Length:   |
| 1.250 inches   |
| Head Style:  |
| Fillister  |
| Head Diameter:   |
| Between 0.389 inches and 0.414 inches  |
| Head Height:   |
| Between 0.161 inches and 0.170 inches  |
| Hole Diameter:   |
| 0.062 inches   |
| Internal Drive Style:  |
| Cross recess type 1  |
| Thread Diameter:   |
| 0.250 inches   |
| Hole Quantity:   |
| 1  |
| Thready Qty Per Inch (tpi):  |
| 28   |
|  |
| Min. Tensile Strength (psi):   |
| Min. Tensile Strength (psi): 55000 pounds per square inch  |
|  |
| 55000 pounds per square inch   |
| 55000 pounds per square inch  Screw Material:  |
| 55000 pounds per square inch  Screw Material:  Steel   |
| 55000 pounds per square inch  Screw Material:  Steel  Screw Material Specification:  |
| 55000 pounds per square inch  Screw Material:  Steel  Screw Material Specification:  Qq-s-633 federal specification single material response   |
| 55000 pounds per square inch  Screw Material:  Steel  Screw Material Specification:  Qq-s-633 federal specification single material response  Screw Surface Treatment:   |
| 55000 pounds per square inch  Screw Material:  Steel  Screw Material Specification:  Qq-s-633 federal specification single material response  Screw Surface Treatment:  Cadmium and chromate   |
| 55000 pounds per square inch  Screw Material:  Steel  Screw Material Specification:  Qq-s-633 federal specification single material response  Screw Surface Treatment:  Cadmium and chromate  Screw Surface Treatment Specification:   |
| 55000 pounds per square inch  Screw Material:  Steel  Screw Material Specification:  Qq-s-633 federal specification single material response  Screw Surface Treatment:  Cadmium and chromate  Screw Surface Treatment Specification:  Qq-p-416 type 2 cl 3 federal specification single treatment response   |
| 55000 pounds per square inch  Screw Material: Steel  Screw Material Specification: Qq-s-633 federal specification single material response  Screw Surface Treatment: Cadmium and chromate  Screw Surface Treatment Specification: Qq-p-416 type 2 cl 3 federal specification single treatment response  Head Hole Configuration Style:                                       |
| 55000 pounds per square inch  Screw Material:  Steel  Screw Material Specification:  Qq-s-633 federal specification single material response  Screw Surface Treatment:  Cadmium and chromate  Screw Surface Treatment Specification:  Qq-p-416 type 2 cl 3 federal specification single treatment response  Head Hole Configuration Style:  Round                            |
| 55000 pounds per square inch  Screw Material:  Steel  Screw Material Specification:  Qq-s-633 federal specification single material response  Screw Surface Treatment:  Cadmium and chromate  Screw Surface Treatment Specification:  Qq-p-416 type 2 cl 3 federal specification single treatment response  Head Hole Configuration Style:  Round  Thread Series Designator: |
| 55000 pounds per square inch  Screw Material: Steel  Screw Material Specification: Qq-s-633 federal specification single material response  Screw Surface Treatment: Cadmium and chromate  Screw Surface Treatment Specification: Qq-p-416 type 2 cl 3 federal specification single treatment response  Head Hole Configuration Style: Round  Thread Series Designator: Unf  |

## NSN 5305-00-722-4710

Machine Screw - Page 2 of 2



| _  |     |         |     |   |  |
|----|-----|---------|-----|---|--|
| 11 | em) | <br>tor | 172 | n |  |
|    |     |         |     |   |  |

No

Fiig:

A500d0