NSN 5305-00-723-2468

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-723-2468 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.188 inches **Fastener Length:** Between 0.157 inches and 0.188 inches **Head Style:** Pan **Head Diameter:** Between 0.155 inches and 0.167 inches **Head Height:** Between 0.053 inches and 0.062 inches **Locking Feature:** Strip threads **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.086 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 140000 pounds per square inch Hardness Rating: 248.0 brinell standard and 328.0 brinell standard Minimum Yield Strength: 85000 pounds per square inch Material: Iron alloy 660 **Material Specification:** Ams 5735 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

--

Unit Of Measure:

NSN 5305-00-723-2468

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0