NSN 5305-00-723-3863



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-723-3863 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.289 inches and 0.453 inches **Fastener Length:** Between 1.219 inches and 1.281 inches **Head Style:** Round extended washer **Head Diameter:** Between 0.427 inches and 0.447 inches **Head Height:** Between 0.096 inches and 0.106 inches **Extended Washer Diameter:** Between 0.490 inches and 0.510 inches **Extended Washer Thickness:** Between 0.028 inches and 0.033 inches **Internal Drive Style:** Cross recess type 1 **End Application:** Spec item **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 62000 pounds per square inch **Screw Material:** Aluminum alloy 2024 **Screw Material Specification:** Qq-a-200/3 federal specification single material response or qq-a-225/6 federal specification single material response **Screw Surface Treatment:** Anodize **Screw Surface Treatment Specification:** Mil-a-8625 military specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

NSN 5305-00-723-3863

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-a-8625 spec.