Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-723-7134

# Thread Class:

2a

**Thread Direction:** 

**Right-hand** 

# Thread Length:

0.375 inches

### Fastener Length:

1.000 inches

#### Head Style:

Fillister

#### Head Diameter:

0.313 inches

## Head Height:

0.123 inches

#### First Diameter From Head:

0.147 inches

## Distance From Largest Bearing Surface Of Head To End Of First Diameter:

0.625 inches

### **Internal Drive Style:**

Slot

### Thread Diameter:

0.190 inches

### Thready Qty Per Inch (tpi):

32

# Externally Relieved Body Diameter Quantity:

1

# Material:

Steel comp 303

### **Material Specification:**

Qq-s-763 federal specification single material response

### Surface Treatment:

Passivate

### Test Data Document:

06540-6240-ss-1032 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

### Thread Series Designator:

Unf

## Shelf Life:

N/a

## Unit Of Measure:

--

#### Demilitarization:

No

Externally Relieved Body Screw - Page 2 of 2



**Fiig:** A003b0

Mil-std (military Standard):

Mil-std-130 spec.