

| Externally Relieved Body Screw - Page 1 of 2 |
|--|
| View Online at https://aerobasegroup.com/nsn/5305-00-724-3415 |
| Thread Class: |
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.421 inches |
| Fastener Length: |
| 0.641 inches |
| Head Style: |
| Flat chamfer |
| Head Diameter: |
| 0.312 inches |
| Head Height: |
| 0.093 inches |
| First Diameter From Head: |
| 0.220 inches |
| Second Diameter From Head: |
| 0.099 inches |
| Distance From Largest Bearing Surface Of Head To End Of First Diameter: |
| 0.142 inches |
| Distance From Largest Bearing Surface Of Head To End Of Second Diameter: |
| 0.220 inches |
| Internal Drive Style: |
| Slot |
| Thread Diameter: |
| 0.138 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Externally Relieved Body Diameter Quantity: |
| 2 |
| Material: |
| Steel comp 303 |
| Material Specification: |
| Qq-s-764 cond a federal specification single material response |
| Surface Treatment: |
| Passivate |
| Thread Series Designator: |
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

NSN 5305-00-724-3415

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0