

View Online at <https://aerobasegroup.com/nsn/5305-00-724-3894>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.312 inches

**Fastener Length:**

0.312 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.257 inches and 0.279 inches

**Locking Feature:**

Patch threads or strip threads

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.138 inches

**Thready Qty Per Inch (tpi):**

32

**Countersink Angle:**

Between 80.0 degrees and 82.0 degrees

**Material:**

Steel comp 301 or steel comp 202 or steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 403 or steel comp 405 or steel comp 410 or steel comp 414 or steel comp 416 or steel comp 416se or steel comp 420 or steel comp 420f or steel comp 430 or steel comp 430f or steel comp 430fse or steel comp 431 or steel comp 440a or steel comp 440b or steel comp 440c or steel comp 446

**Material Specification:**

66 federal standard single material response

**Surface Treatment:**

Passivate

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0