NSN 5305-00-724-6705

Shoulder Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-724-6705



2a Thread Direction: Right-hand Thread Length: Between 0.359 inches and 0.391 inches Fastener Length: Between 0.539 inches and 0.591 inches Head Style: Round w/wrench flats Head Diameter:

Thread Class:

Between 0.176 inches and 0.183 inches

Head Height:

Between 0.222 inches and 0.232 inches

Width Between Flats:

Between 0.060 inches and 0.070 inches

Shoulder Diameter:

0.060 inches first shoulder and 0.070 inches first shoulder

Shoulder Length:

0.180 inches first shoulder and 0.200 inches first shoulder

Internal Drive Style:

W/o internal drive

Thread Diameter:

0.112 inches

Thready Qty Per Inch (tpi):

40

Shoulder Shape:

Round first shoulder

Color:

Black

Material:

Steel comp 303se

Material Specification:

Astma 582 assn standard single material response

Surface Treatment:

Passivate and oxide

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response and mil-c-13924 cl 2 military specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

NSN 5305-00-724-6705

Shoulder Screw - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.

