# NSN 5305-00-725-1634

Machine Screw - Page 1 of 1

View Online at https://aerobasegroup.com/nsn/5305-00-725-1634



#### Thread Class:

3a

**Thread Direction:** 

Right-hand

## Thread Length:

Between 0.344 inches and 0.484 inches

## Fastener Length:

Between 1.891 inches and 1.938 inches

### Head Style:

Flat countersunk

## Head Diameter:

Between 0.283 inches and 0.332 inches

## Internal Drive Style:

Cross recess type 1

## Thread Diameter:

0.164 inches

# Thready Qty Per Inch (tpi):

32

### Min. Tensile Strength (psi):

125000 pounds per square inch

### Hardness Rating:

Between 26.0 rockwell c and 32.0 rockwell c

### Countersink Angle:

Between 99.0 degrees and 101.0 degrees

#### **Screw Material:**

Steel comp 8630 or steel comp 4037

### Screw Material Specification:

Mil-s-6050 military specification 1st material response or ams 6300 assn standard 2nd material response

### Screw Surface Treatment:

Cadmium

### **Thread Series Designator:**

Unc

### Shelf Life:

N/a

## Unit Of Measure:

---

#### Demilitarization:

No

Fiig:

A500d0

## Mil-std (military Standard):

Mil-s-6050 spec.