NSN 5305-00-725-4191

Machine Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-725-4191

| Thread Direction: Right-hand Thread Length: Between 0.464 inches and 0.500 inches Fastener Length: 0.500 inches Head Style: Flat countersunk Head Diameter: Between 0.147 inches and 0.172 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.086 inches Thread Diameter: 0.096 inches Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A50000 | Thread Class: |
|--|--|
| Right-hand Thread Length: Between 0.464 inches and 0.500 inches Fastener Length: 0.500 inches Head Style: Flat countersunk Head Diameter: Between 0.147 inches and 0.172 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.086 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 80000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degrees Screw Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 Screw Material Specification: 66 federal standard all material responses Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig: | 2a |
| Thread Length: Between 0.464 inches and 0.500 inches Fastener Length: 0.500 inches Head Style: Flat countersunk Head Diameter: Between 0.147 inches and 0.172 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.086 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 80000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degrees Screw Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 Screw Material Specification: 66 federal standard all material responses Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | Thread Direction: |
| Between 0.464 inches and 0.500 inches Fastener Length: 0.500 inches Head Style: Flat countersunk Head Diameter: Between 0.147 inches and 0.172 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.086 inches Thread Diameter: 0.086 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 80000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degrees Screw Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 Screw Material Specification: 66 federal standard all material responses Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig: | Right-hand |
| Fastener Length: 0.500 inches Head Style: Flat countersunk Head Diameter: Between 0.147 inches and 0.172 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.086 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 80000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degrees Screw Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 Screw Material Specification: 66 federal standard all material responses Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig: | Thread Length: |
| Head Style: Flat countersunk Head Diameter: Between 0.147 inches and 0.172 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.086 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 80000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degrees Screw Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 Screw Material Specification: 66 federal standard all material responses Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: | Between 0.464 inches and 0.500 inches |
| Head Style: Flat countersunk Head Diameter: Between 0.147 inches and 0.172 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.086 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 80000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degrees Screw Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 Screw Material Specification: 66 federal standard all material responses Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: | Fastener Length: |
| Flat countersunk Head Diameter: Between 0.147 inches and 0.172 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.086 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 80000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degrees Screw Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 Screw Material Specification: 66 federal standard all material responses Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: | 0.500 inches |
| Head Diameter: Between 0.147 inches and 0.172 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.086 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 80000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degrees Screw Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 Screw Material Specification: 66 federal standard all material responses Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: | Head Style: |
| Internal Drive Style: Cross recess type 1 Thread Diameter: 0.086 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 80000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degrees Screw Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 Screw Material Specification: 66 federal standard all material responses Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | Flat countersunk |
| Internal Drive Style: Cross recess type 1 Thread Diameter: 0.086 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 80000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degrees Screw Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 Screw Material Specification: 66 federal standard all material responses Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: | Head Diameter: |
| Cross recess type 1 Thread Diameter: 0.086 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 80000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degrees Screw Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 Screw Material Specification: 66 federal standard all material responses Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: | Between 0.147 inches and 0.172 inches |
| Thread Diameter: 0.086 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 80000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degrees Screw Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 Screw Material Specification: 66 federal standard all material responses Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: | Internal Drive Style: |
| Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 80000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degrees Screw Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 Screw Material Specification: 66 federal standard all material responses Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fitig: | Cross recess type 1 |
| Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 80000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degrees Screw Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 Screw Material Specification: 66 federal standard all material responses Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fitig: | Thread Diameter: |
| Min. Tensile Strength (psi): 80000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degrees Screw Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 Screw Material Specification: 66 federal standard all material responses Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: | 0.086 inches |
| Min. Tensile Strength (psi): 80000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degrees Screw Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 Screw Material Specification: 66 federal standard all material responses Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | Thready Qty Per Inch (tpi): |
| 80000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degrees Screw Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 Screw Material Specification: 66 federal standard all material responses Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | 56 |
| Countersink Angle: Between 80.0 degrees and 82.0 degrees Screw Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 Screw Material Specification: 66 federal standard all material responses Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | Min. Tensile Strength (psi): |
| Between 80.0 degrees and 82.0 degrees Screw Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 Screw Material Specification: 66 federal standard all material responses Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | 80000 pounds per square inch |
| Screw Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 Screw Material Specification: 66 federal standard all material responses Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | Countersink Angle: |
| Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 Screw Material Specification: 66 federal standard all material responses Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | Between 80.0 degrees and 82.0 degrees |
| Screw Material Specification: 66 federal standard all material responses Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | Screw Material: |
| 66 federal standard all material responses Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 |
| Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | Screw Material Specification: |
| Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | 66 federal standard all material responses |
| Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | Screw Surface Treatment: |
| Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | Passivate |
| Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | Screw Surface Treatment Specification: |
| Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | Qq-p-35 federal specification single treatment response |
| Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | Thread Series Designator: |
| N/a Unit Of Measure: Demilitarization: No Fiig: | Unc |
| Unit Of Measure: Demilitarization: No Fiig: | Shelf Life: |
| Demilitarization: No Fiig: | N/a |
| No Fiig: | Unit Of Measure: |
| No Fiig: | |
| Fiig: | Demilitarization: |
| - | No |
| A500d0 | Fiig: |
| | A500d0 |