## NSN 5305-00-726-2556

Hexagon Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-726-2556 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 1.500 inches and 1.688 inches **Fastener Length:** 3.250 inches **Head Style:** Hexagon **Head Height:** Between 0.378 inches and 0.403 inches Width Between Flats: Between 0.922 inches and 0.938 inches **End Application:** Mrap buffalo mk2a2 **Thread Diameter:** 0.625 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 150000 pounds per square inch **Hardness Rating:** 32.0 rockwell c and 38.0 rockwell c Minimum Yield Strength: 120000 pounds per square inch Material: Steel **Material Specification:** Sae gr 8 assn standard single material response **Surface Treatment:** Zinc and chromate **Surface Treatment Specification:** Astm b633 type 2 sc 3 assn standard single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

No

## NSN 5305-00-726-2556

Hexagon Head Cap Screw - Page 2 of 2



Fiig:

A003b0