

View Online at <https://aerobasegroup.com/nsn/5305-00-727-0503>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.624 inches

Fastener Length:

Between 2.516 inches and 2.546 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.220 inches and 0.230 inches

Head Height:

Between 0.220 inches and 0.280 inches

First Diameter From Head:

Between 0.130 inches and 0.150 inches

Second Diameter From Head:

Between 0.220 inches and 0.230 inches

Third Diameter From Head:

Between 0.091 inches and 0.097 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 1.119 inches and 1.159 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

Between 1.214 inches and 1.224 inches

Distance From Largest Bearing Surface Of Head To End Of Third Diameter:

Between 1.902 inches and 1.912 inches

Internal Drive Style:

Slot

Thread Diameter:

0.138 inches

Thready Qty Per Inch (tpi):

32

Externally Relieved Body Diameter Quantity:

1

Material:

Steel comp 303

Material Specification:

Astm a582 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-f-14072, finish e300 military specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.