NSN 5305-00-728-1492

Socket Head Cap Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-728-1492

| Thread Class: | |
|--------------------|--|
| 2a | |
| Thread Direction | : |
| Right-hand | |
| Thread Length: | |
| 0.280 inches | |
| Fastener Length: | |
| Between 0.235 inc | ches and 0.280 inches |
| Head Style: | |
| Binding | |
| Head Diameter: | |
| Between 0.272 inc | ches and 0.281 inches |
| Head Height: | |
| Between 0.071 inc | ches and 0.075 inches |
| Locking Feature: | |
| Pellet threads | |
| Internal Drive Sty | rle: |
| Cross recess type | 1 |
| Thread Diameter | : |
| 0.112 inches | |
| Thready Qty Per | Inch (tpi): |
| 40 | |
| Min. Tensile Stre | ngth (psi): |
| 160000 pounds pe | er square inch |
| Special Features | : |
| Furnished w/1 poly | ytetrafluoroethylene washer and 1 o ring |
| Material: | |
| Steel | |
| Surface Treatme | nt: |
| Cadmium and chi | romate |
| Thread Series De | signator: |
| Unc | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A003b0 | |