NSN 5305-00-730-7890



Shoulder Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-730-7890 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.360 inches **Fastener Length:** 0.940 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.386 inches and 0.390 inches **Shoulder Diameter:** 0.254 inches first shoulder and 0.256 inches first shoulder **Shoulder Length:** 0.370 inches first shoulder **Shank Unthreaded Hole Diameter:** 0.070 inches first hole **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Hardness Rating: 30.0 rockwell c and 36.0 rockwell c **Countersink Angle:** 90.0 degrees Distance From Head Largest Bearing Surface To Shank Hole Center: 0.840 inches first hole **Shoulder Shape:** Round first shoulder Material: Steel comp 1330 or steel comp 1340 **Surface Treatment:** Phosphate **Thread Series Designator:** Unf Shelf Life: N/a

Unit Of Measure:

NSN 5305-00-730-7890

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0