# NSN 5305-00-733-3038

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-733-3038



### **Thread Class:**

3a

**Thread Direction:** 

Right-hand

### Thread Length:

Between 0.376 inches and 0.516 inches

#### Fastener Length:

Between 2.391 inches and 2.438 inches

#### **Head Style:**

Flat countersunk

#### Head Diameter:

Between 0.327 inches and 0.385 inches

#### Internal Drive Style:

Cross recess type 1

#### Thread Diameter:

0.190 inches

### Thready Qty Per Inch (tpi):

32

### Min. Tensile Strength (psi):

125000 pounds per square inch

#### Hardness Rating:

Between 26.0 rockwell c and 32.0 rockwell c

#### **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

#### Screw Material:

Steel comp 8640 or steel comp 4037

#### Screw Material Specification:

Mil-s-6050 military specification 1st material response or ams 6300 assn standard 2nd material response

#### Screw Surface Treatment:

Cadmium and chromate

# Screw Surface Treatment Specification:

Qq-p-416 type 2 cl 3 federal specification single treatment response

### **Thread Series Designator:**

Unf

#### Shelf Life:

N/a

## Unit Of Measure:

---

# Demilitarization:

No

#### Fiig:

A500d0

# NSN 5305-00-733-3038

Machine Screw - Page 2 of 2

# Mil-std (military Standard):

Mil-s-6050 spec.

