NSN 5305-00-733-8552



Externally Relieved Body Screw - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5305-00-733-8552 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.188 inches **Fastener Length:** 0.688 inches **Head Style:** Fillister **Head Diameter:** Between 0.293 inches and 0.313 inches **Head Height:** Between 0.107 inches and 0.123 inches First Diameter From Head: 0.149 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.500 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1022 or steel comp 1025 or steel comp 1116 or steel comp 1116 or steel comp 1117 or steel comp 1118 or steel comp 1119 **Material Specification:** Astm a576 assn standard 1st material response or astm a675 assn standard 1st material response or astm a108 assn standard 1st material response or astm a108 assn standard 2nd material response or astm a575 assn standard 3rd material response or astm a576 assn standard 3rd material response or astm a675 assn standard 3rd material response or astm a108 assn standard 3rd material response or astm a108 assn standard 4th material response or astm a575 assn standard 5th material response or astm a576 assn standard 5th material response or astm a675 assn standard 5th material response or astm a108 assn standard 5th material response or qq-s-637 assn standard 6th material response **Surface Treatment:** Cadmium **Thread Series Designator:** Unf Shelf Life: N/a

Demilitarization:

Unit Of Measure: