NSN 5305-00-736-3466

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-736-3466 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.578 inches **Fastener Length:** Between 4.400 inches and 4.420 inches **Head Style:** Flat chamfer **Head Diameter:** 0.281 inches **Head Height:** Between 0.490 inches and 0.500 inches **First Diameter From Head:** 0.187 inches **Second Diameter From Head:** 0.125 inches **Third Diameter From Head:** 0.187 inches **Fourth Diameter From Head:** 0.144 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.547 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.582 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 0.622 inches Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter: **3.832** inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity: Product Name:**

Navy special project

Special Features:

Color red federal standard 595 no. 21105

NSN 5305-00-736-3466

Externally Relieved Body Screw - Page 2 of 2



Material:
Steel comp 303
Surface Treatment:
Passivate or paint
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A003b0