NSN 5305-00-736-3471

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-736-3471 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: **4.219 inches Fastener Length:** 4.938 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.297 inches and 0.312 inches **Head Height:** 0.203 inches **First Diameter From Head:** Between 0.145 inches and 0.150 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.719 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Product Name:** Navy special project **Special Features:** Thd interrupted by undercut and cone point Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life:

N/a

NSN 5305-00-736-3471

Externally Relieved Body Screw - Page 2 of 2



Unit Of	Measure:
---------	----------

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.