## NSN 5305-00-736-3825

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-736-3825 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.085 inches **Fastener Length:** 0.180 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.155 inches and 0.167 inches **Head Height:** Between 0.045 inches and 0.053 inches **First Diameter From Head:** Between 0.082 inches and 0.086 inches **Second Diameter From Head:** Between 0.062 inches and 0.064 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.065 inches and 0.085 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.085 inches and 0.105 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.086 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Stainless steel **Material Specification:** Qq-s-763 federal specification single material response **Surface Treatment: Passivate Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

--

## NSN 5305-00-736-3825

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0