## NSN 5305-00-752-7988

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-752-7988 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.531 inches **Fastener Length:** 2.062 inches **Head Style:** Flat chamfer **Head Diameter:** 0.625 inches **Head Height:** 0.250 inches **Shoulder Diameter:** 0.484 inches first shoulder and 0.516 inches first shoulder **Shoulder Length:** 1.437 inches first shoulder **Shank Unthreaded Hole Diameter:** 0.125 inches first hole **Internal Drive Style:** Slot **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): 16 Distance From Head Largest Bearing Surface To Shank Hole Center: 0.094 inches first hole **Shoulder Shape:** Round first shoulder **Special Features:** 0.250 in. Diameter by 0.094 in. W undercut on thd end at shoulder **Surface Treatment:** Cadmium and chromate and zinc and chromate **Surface Treatment Specification:** Qq-p-416 type 2 cl 1 federal specification 1st treatment response or qq-z-325 type 2 cl 1 federal specification 2nd treatment response **Thread Series Designator:** Unc Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5305-00-752-7988

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0