--

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-753-4105

	https://aerobasegroup.com/nsn/5305-00-753-4105
Thread Class:	
2a	
Thread Direction	on:
Right-hand	
Thread Length	
0.358 inches	
Fastener Lengt	h:
0.438 inches	
Head Style:	
Fillister	
Head Diameter	:
Between 0.292	inches and 0.313 inches
Head Height:	
Between 0.118	inches and 0.130 inches
Washer Quanti	ty:
1	
Internal Drive S	Style:
Cross recess ty	be 1
Thread Diamet	er:
0.190 inches	
Thready Qty Pe	er Inch (tpi):
24	
Hardness Ratir	ng:
45.0 rockwell c	primary washer and 50.0 rockwell c primary washer
Primary Washe	er Outside Diameter:
Between 0.283	inches and 0.297 inches
Primary Washe	r Style:
Split helical ring	
Primary Washe	er Material Thickness:
0.040 inches	
Material:	
Steel comp 101	0 fastener or steel comp 1011 fastener or steel comp 1013 fastener or steel comp 1015 fastener or steel comp 1016 fastener
or steel comp 10	017 fastener or steel comp 1018 fastener or steel comp 1019 fastener or steel comp 1020 fastener
Surface Treatm	ient:
Cadmium or zir	
Surface Treatm	ent Specification:
Qq-p-416, type	1, cl 3 federal specification 1st treatment response or qq-z-325, type 1, cl 3 federal specification 2nd treatment response
Thread Series	Designator:
Unc	
Shelf Life:	
N/a	
Unit Of Measur	e:

NSN 5305-00-753-4105

Assembled Washer Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

