NSN 5305-00-754-2047

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-754-2047 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.406 inches and 0.438 inches **Fastener Length:** Between 0.797 inches and 0.807 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.498 inches and 0.502 inches **Head Height:** Between 0.120 inches and 0.130 inches **First Diameter From Head:** Between 0.243 inches and 0.245 inches **Second Diameter From Head:** Between 0.120 inches and 0.130 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.297 inches and 0.307 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.375 inches and 0.385 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Thread Series Designator:** Unc Shelf Life: N/a

Unit Of Measure:

NSN 5305-00-754-2047

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0