## NSN 5305-00-754-3060

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-754-3060

Thread Class:						
2a						
Thread Direction:						
Right-hand						
Thread Length:						
Between 0.313 inches and 0.375 inches						
Fastener Length:						
0.375 inches						
Head Style:						
Fillister						
Head Diameter:						
Between 0.208 inches and 0.226 inches						
Head Height:						
Between 0.089 inches and 0.096 inches						
Hole Diameter:						
0.046 inches						
Internal Drive Style:						
Cross recess type 1						
Thread Diameter:						
0.138 inches						
Hole Quantity:						
1						
Thready Qty Per Inch (tpi):						
32						
Min. Tensile Strength (psi):						
80000 pounds per square inch						
Screw Material:						
Steel comp 410 or steel comp 416						
Screw Material Specification:						
Screw Material Specification:  Qq-s-763 federal specification all material responses						
•						
Qq-s-763 federal specification all material responses						
Qq-s-763 federal specification all material responses  Screw Surface Treatment:						
Qq-s-763 federal specification all material responses  Screw Surface Treatment:  Passivate						
Qq-s-763 federal specification all material responses  Screw Surface Treatment:  Passivate  Screw Surface Treatment Specification:						
Qq-s-763 federal specification all material responses  Screw Surface Treatment:  Passivate  Screw Surface Treatment Specification:  Qq-p-35 federal specification single treatment response						
Qq-s-763 federal specification all material responses  Screw Surface Treatment:  Passivate  Screw Surface Treatment Specification:  Qq-p-35 federal specification single treatment response  Head Hole Configuration Style:						
Qq-s-763 federal specification all material responses  Screw Surface Treatment:  Passivate  Screw Surface Treatment Specification:  Qq-p-35 federal specification single treatment response  Head Hole Configuration Style:  Round						
Qq-s-763 federal specification all material responses  Screw Surface Treatment:  Passivate  Screw Surface Treatment Specification:  Qq-p-35 federal specification single treatment response  Head Hole Configuration Style:  Round  Thread Series Designator:						
Qq-s-763 federal specification all material responses  Screw Surface Treatment:  Passivate  Screw Surface Treatment Specification:  Qq-p-35 federal specification single treatment response  Head Hole Configuration Style:  Round  Thread Series Designator:  Unc						
Qq-s-763 federal specification all material responses  Screw Surface Treatment:  Passivate  Screw Surface Treatment Specification:  Qq-p-35 federal specification single treatment response  Head Hole Configuration Style:  Round  Thread Series Designator:  Unc  Specification Or Standard:						

## NSN 5305-00-754-3060

Machine Screw - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A500d0