NSN 5305-00-754-3133

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-754-3133 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 1.037 inches and 1.130 inches **Fastener Length:** Between 1.109 inches and 1.141 inches **Head Style:** Fillister **Head Diameter:** Between 0.292 inches and 0.313 inches **Head Height:** Between 0.118 inches and 0.130 inches **First Diameter From Head:** Between 0.134 inches and 0.144 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.721 inches and 0.747 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 130000 pounds per square inch **Externally Relieved Body Diameter Quantity:** Material: Steel comp 4140 **Material Specification:** Astm a547 assn standard 1st material response **Surface Treatment:** Paint head **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

NSN 5305-00-754-3133

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0