NSN 5305-00-754-3180

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-754-3180 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.182 inches and 0.192 inches **Fastener Length:** Between 0.469 inches and 0.500 inches **Head Style:** Pan **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** Between 0.087 inches and 0.097 inches **First Diameter From Head:** 0.138 inches **Second Diameter From Head:** Between 0.083 inches and 0.093 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.027 inches and 0.037 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.271 inches and 0.291 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 80000 pounds per square inch **Externally Relieved Body Diameter Quantity:** Material: Stainless steel **Surface Treatment: Passivate Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-00-754-3180

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0