Externally Relieved Body Screw - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-00-754-3180

Threa	d Class:
2a	
Threa	d Direction:
Right-I	hand
Threa	d Length:
Betwe	en 0.182 inches and 0.192 inches
Faster	ner Length:
Betwe	en 0.469 inches and 0.500 inches
Head	Style:
Pan	
Head	Diameter:
Betwe	en 0.256 inches and 0.270 inches
Head	Height:
Betwe	en 0.087 inches and 0.097 inches
First D	Diameter From Head:
0.138	inches
Secon	d Diameter From Head:
Betwe	en 0.083 inches and 0.093 inches
Distar	ce From Largest Bearing Surface Of Head To End Of First Diameter:
Betwe	en 0.027 inches and 0.037 inches
Distar	ce From Largest Bearing Surface Of Head To End Of Second Diameter:
Betwe	en 0.271 inches and 0.291 inches
Intern	al Drive Style:
Cross	recess type 1
Threa	d Diameter:
0.138	inches
Threa	dy Qty Per Inch (tpi):
32	
Min. T	ensile Strength (psi):
80000	pounds per square inch
Exterr	nally Relieved Body Diameter Quantity:
2	
Materi	al:
Stainle	ess steel
Surfac	ce Treatment:
Passiv	rate
Threa	d Series Designator:
Unc	
Shelf	Life:
N/a	
Unit O	of Measure:

NSN 5305-00-754-3180

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0