## NSN 5305-00-756-5736

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-756-5736 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.131 inches and 0.141 inches **Fastener Length:** Between 0.456 inches and 0.476 inches **Head Style:** Pan **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.070 inches and 0.080 inches **First Diameter From Head:** Between 0.067 inches and 0.072 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.315 inches and 0.345 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Olive drab enamel federal standard 595 color no. X24087 Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

--

## NSN 5305-00-756-5736

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0