## NSN 5305-00-758-0959

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-758-0959

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
0.500 inches
Fastener Length:
0.550 inches
Head Style:
Flat chamfer
Head Diameter:
0.700 inches
Head Height:
Between 0.122 inches and 0.135 inches
Shoulder Diameter:
0.428 inches first shoulder and 0.430 inches first shoulder
Shoulder Length:
0.105 inches first shoulder and 0.108 inches first shoulder
Internal Drive Style:
Hexagon
Thread Diameter:
0.312 inches
Width Across Flats:
Between 0.219 inches and 0.221 inches
Thready Qty Per Inch (tpi):
24
Hardness Rating:
35.0 rockwell c and 45.0 rockwell c
Shoulder Shape:
Round first shoulder
Special Features:
Nylon pellet in thd
Material:
Steel comp 4340
Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416 type 1 cl 2 federal specification single treatment response
Thread Series Designator:
Unf
Shelf Life:
N/a

## NSN 5305-00-758-0959

Shoulder Screw - Page 2 of 2



ı	1	n	iŧ	0	: N/	lea			_	
ı	u	n	IT	OI	١V	ıea	เรเ	JI	е	:

--

Demilitarization:

No

Fiig:

A003b0