NSN 5305-00-759-1120

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-759-1120 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.187 inches **Fastener Length:** 0.375 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.308 inches and 0.332 inches First Diameter From Head: 0.164 inches **Second Diameter From Head:** 0.110 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.100 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.188 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 1010 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Astm a576 assn standard single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-00-759-1120

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0