## NSN 5305-00-760-2804

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-760-2804

Thread Class
Thread Class:
3a Thread Biractions
Thread Direction:
Right-hand
Thread Length:
Between 0.288 inches and 0.391 inches
Fastener Length:
Between 0.359 inches and 0.391 inches
Head Style:
Round extended washer  Head Diameter:
Between 0.427 inches and 0.447 inches
Head Height:
Between 0.096 inches and 0.106 inches
Extended Washer Diameter:
Between 0.490 inches and 0.510 inches
Extended Washer Thickness:
Between 0.028 inches and 0.033 inches
Internal Drive Style:
Cross recess type 1  Thread Diameter:
0.250 inches Thready Oty Per Inch (tpi):
Thready Qty Per Inch (tpi): 28
Min. Tensile Strength (psi):
125000 pounds per square inch
Hardness Rating:
Between 26.0 rockwell c and 32.0 rockwell c
Screw Material:
Steel comp 8630 or steel comp 4037
Screw Material Specification:
Mil-s-6050 military specification 1st material response or ams 6300 assn standard 2nd material response
Screw Surface Treatment:
Cadmium
Screw Surface Treatment Specification:
Qq-p-416 federal specification single treatment response
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:

## NSN 5305-00-760-2804

Machine Screw - Page 2 of 2



_		••	• •				
n	em	ш	112	riz	2†1	n	٠.

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-s-6050 spec.