NSN 5305-00-760-8081

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-760-8081 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.296 inches and 0.328 inches **Fastener Length:** Between 1.296 inches and 1.328 inches **Head Style:** Binding **Head Diameter:** Between 0.275 inches and 0.290 inches **Head Height:** Between 0.071 inches and 0.080 inches **First Diameter From Head:** Between 0.092 inches and 0.095 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.968 inches and 1.032 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Cone point Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072, finish e300 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

Unit Of Measure:

NSN 5305-00-760-8081

Externally Relieved Body Screw - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.