NSN 5305-00-761-1670



Shoulder Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-761-1670 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.334 inches and 0.350 inches **Fastener Length:** Between 0.770 inches and 0.781 inches **Head Style:** Pan no. 2 **Head Diameter:** 0.500 inches **Head Height:** Between 0.099 inches and 0.110 inches **Shoulder Diameter:** 0.217 inches first shoulder and 0.219 inches first shoulder **Shoulder Length:** 0.431 inches first shoulder and 0.436 inches first shoulder **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 24 **Shoulder Shape:** Round first shoulder Material: Steel comp 302 or steel comp 304 or steel comp 316 or steel comp 303 or steel comp 303se **Material Specification:** Qq-s-763, cond b mfr ref 1st material response or qq-s-763, cond b mfr ref 2nd material response or qq-s-763, cond b mfr ref 3rd material response or qq-s-764, cond b mfr ref 4th material response or qq-s-764, cond b mfr ref 5th material response **Surface Treatment: Passivate Surface Treatment Specification:** 3023, fscm 92674 mfr ref single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

No

Unit Of Measure:

Demilitarization:

NSN 5305-00-761-1670 Shoulder Screw - Page 2 of 2



Fiig:

A003b0