Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-762-6040

view Online at https://aeiobasegioup.com/nsn/3303-00-702-0040
Thread Class:
За
Thread Direction:
Right-hand
Thread Length:
Between 0.548 inches and 0.610 inches
Fastener Length:
Between 0.610 inches and 0.640 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.262 inches and 0.270 inches
Head Height:
Between 0.159 inches and 0.164 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.164 inches
Width Across Flats:
Between 0.141 inches and 0.143 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
80000 pounds per square inch
Hardness Rating:
80.0 rockwell b
Minimum Yield Strength:
30000 pounds per square inch
Material:
Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Shelf Life:
Unit Of Measure:
 Demiliterization
Demilitarization:
No

NSN 5305-00-762-6040

Socket Head Cap Screw - Page 2 of 2

Fiig: A003b0

