

View Online at <https://aerobasegroup.com/nsn/5305-00-762-6211>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.187 inches

Fastener Length:

1.082 inches

Head Style:

Flat fillister

Head Diameter:

0.451 inches

Head Height:

0.520 inches

Internal Drive Style:

Slot

End Application:

Helicopter, carrier based asw, sh-60f; ticonderoga class cg (47); computer display set, an/uyq-2 (v); spruance class dd (963); sonar acoustic miscellaneous; support equipment, b-52 aircraft; helicopter, uscg search and rescue, hh-60j; deep submergence systems programs(dssp) ; helicopter, search and rescue, hh-60h

Material Accommodated Thickness:

Between 0.188 inches and 0.312 inches

Thread Diameter:

0.190 inches

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

32

Special Features:

Turn-loc, high profile; optional recess, .031 radial flt

Material:

Steel comp 302

Material Specification:

Ams5636 assn standard 1st material response or mil-c-13924, class 4 military specification 2nd material response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.