

View Online at <https://aerobasegroup.com/nsn/5305-00-762-6211>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.187 inches

**Fastener Length:**

1.082 inches

**Head Style:**

Flat fillister

**Head Diameter:**

0.451 inches

**Head Height:**

0.520 inches

**Internal Drive Style:**

Slot

**End Application:**

Helicopter, carrier based asw, sh-60f; ticonderoga class cg (47); computer display set, an/uyq-2 (v); spruance class dd (963); sonar acoustic miscellaneous; support equipment, b-52 aircraft; helicopter, uscg search and rescue, hh-60j; deep submergence systems programs(dssp) ; helicopter, search and rescue, hh-60h

**Material Accommodated Thickness:**

Between 0.188 inches and 0.312 inches

**Thread Diameter:**

0.190 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

32

**Special Features:**

Turn-loc, high profile; optional recess, .031 radial flt

**Material:**

Steel comp 302

**Material Specification:**

Ams5636 assn standard 1st material response or mil-c-13924, class 4 military specification 2nd material response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-c-13924 spec.