NSN 5305-00-762-7475



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-762-7475 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.227 inches and 0.257 inches **Fastener Length:** 1.500 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.491 inches and 0.507 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 150000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Steel comp e4340 **Screw Material Specification:** Mil-s-5000 military specification single material response **Screw Surface Treatment:** Cadmium **Screw Surface Treatment Specification:** Mac ps 13101 type 1 cl c fscm 76301 mfr ref single treatment response **Test Data Document:** 76301-macp.S.21201 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:**

Fiig: A500d0

No

Demilitarization:

NSN 5305-00-762-7475

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-5000 spec.