## NSN 5305-00-763-6960

Machine Screw - Page 1 of 2

**Thread Class:** 

View Online at https://aerobasegroup.com/nsn/5305-00-763-6960



## 2a **Thread Direction: Right-hand Thread Length:** Between 0.036 inches and 0.140 inches Fastener Length: Between 0.157 inches and 0.188 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.244 inches and 0.279 inches **Head Height:** Between 0.048 inches and 0.059 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 80000 pounds per square inch **Countersink Angle:** Between 80.0 degrees and 82.0 degrees **Screw Material:** Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Screw Material Specification:** 66 federal standard all material responses **Screw Surface Treatment:** Passivate **Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc **Specification Or Standard:** 3 type and 2c style Shelf Life: N/a Unit Of Measure: **Demilitarization:** No

## NSN 5305-00-763-6960

Machine Screw - Page 2 of 2

Fiig: A500d0

