NSN 5305-00-763-9405Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-763-9405
Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
0.276 inches
Fastener Length:
Between 3.886 inches and 3.917 inches
Head Style:
Pan no. 2
Head Diameter:
Between 0.306 inches and 0.322 inches
Head Height:
Between 0.105 inches and 0.115 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.164 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
Between 36.0 rockwell c and 40.0 rockwell c
Product Name:
Navy special project
Screw Material:
Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740
Screw Material Specification:
Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military
specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material response
Screw Surface Treatment:
Cadmium and chromate
Screw Surface Treatment Specification:
Qq-p-416, type 2 cl 3 federal specification all treatment responses
Thread Series Designator:
Unc
Specification Data:
80205-nas623 professional/industrial association standard
Shelf Life:
N/a

Unit Of Measure:

NSN 5305-00-763-9405

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-s-5626 spec.