## NSN 5305-00-763-9608

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-763-9608

Thread Class:
3a 
Thread Direction:
Right-hand
Thread Length:
Between 0.376 inches and 0.416 inches
Fastener Length:
Between 0.427 inches and 0.447 inches
Head Style:
Flat countersunk undercut
Head Diameter:
Between 0.231 inches and 0.279 inches
Head Height:
Between 0.031 inches and 0.051 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.112 inches
Thready Qty Per Inch (tpi):
40
Min. Tensile Strength (psi):
160000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Product Name:
Navy special project
Screw Material:
Steel comp 4037
Screw Material Specification:
Qq-s-624 federal specification single material response
Screw Surface Treatment:
Cadmium and chromate
Screw Surface Treatment Specification:
Qq-p-416, type 2 cl 3 federal specification all treatment responses
Special Features:
Furnished with one polytetrafluoroethylene washer and one o-ring
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:

## NSN 5305-00-763-9608

Machine Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A500d0

