NSN 5305-00-764-1847

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-764-1847 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.250 inches **Fastener Length:** 0.687 inches **Head Style:** Pan no. 2 **Head Diameter:** 0.314 inches **Head Height:** 0.090 inches **First Diameter From Head:** 0.164 inches **Second Diameter From Head:** 0.125 inches **Third Diameter From Head:** 0.080 inches **Fourth Diameter From Head:** 0.125 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.250 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.347 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 0.387 inches Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter: 0.437 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 4 Material: Stainless steel

Passivate

Surface Treatment:

NSN 5305-00-764-1847

Externally Relieved Body Screw - Page 2 of 2



inread Series Designator
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0