Externally Relieved Body Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-764-2770

| Ihread | Class: |
|----------|--------------------------------------------------------------------------------|
| 2a | |
| Thread | Direction: |
| Right-ha | and |
| Thread | Length: |
| 0.220 in | ches |
| Fastene | er Length: |
| 0.660 in | ches |
| Head St | yle: |
| Knurled | no. 1 |
| Head D | ameter: |
| 0.440 in | ches |
| Head H | eight: |
| 0.260 in | ches |
| First Di | ameter From Head: |
| 0.135 in | ches |
| Distanc | e From Largest Bearing Surface Of Head To End Of First Diameter: |
| 0.440 in | ches |
| Internal | Drive Style: |
| Slot | |
| Thread | Diameter: |
| 0.190 in | ches |
| Thready | / Qty Per Inch (tpi): |
| 24 | |
| Externa | Ily Relieved Body Diameter Quantity: |
| 1 | |
| Materia | : |
| Steel co | mp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 |
| Materia | I Specification: |
| | al standard all material responses |
| | Treatment: |
| Passiva | te |
| | Series Designator: |
| Unc | |
| Shelf Li | fe: |
| N/a | |
| | Measure: |
| | |
| | arization: |
| No | |
| Fiig: | |
| | |