NSN 5305-00-764-3036

Machine Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-764-3036

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.641 inches
Fastener Length:
1.516 inches
Head Style:
Flat countersunk undercut
Head Diameter:
Between 0.755 inches and 0.760 inches
Head Height:
Between 0.114 inches and 0.116 inches
Internal Drive Style:
High-torque
Thread Diameter:
0.375 inches
Features Provided:
O ring
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
Min. Tensile Strength (psi): 180000 pounds per square inch
180000 pounds per square inch
180000 pounds per square inch Countersink Angle:
180000 pounds per square inch Countersink Angle: 100.0 degrees
180000 pounds per square inch Countersink Angle: 100.0 degrees Screw Material:
180000 pounds per square inch Countersink Angle: 100.0 degrees Screw Material: Steel comp 4140 or steel comp 4340 or steel comp 8740
180000 pounds per square inch Countersink Angle: 100.0 degrees Screw Material: Steel comp 4140 or steel comp 4340 or steel comp 8740 Screw Surface Treatment:
180000 pounds per square inch Countersink Angle: 100.0 degrees Screw Material: Steel comp 4140 or steel comp 4340 or steel comp 8740 Screw Surface Treatment: Cadmium
180000 pounds per square inch Countersink Angle: 100.0 degrees Screw Material: Steel comp 4140 or steel comp 4340 or steel comp 8740 Screw Surface Treatment: Cadmium Thread Series Designator:
180000 pounds per square inch Countersink Angle: 100.0 degrees Screw Material: Steel comp 4140 or steel comp 4340 or steel comp 8740 Screw Surface Treatment: Cadmium Thread Series Designator: Unf
180000 pounds per square inch Countersink Angle: 100.0 degrees Screw Material: Steel comp 4140 or steel comp 4340 or steel comp 8740 Screw Surface Treatment: Cadmium Thread Series Designator: Unf Shelf Life:
180000 pounds per square inch Countersink Angle: 100.0 degrees Screw Material: Steel comp 4140 or steel comp 4340 or steel comp 8740 Screw Surface Treatment: Cadmium Thread Series Designator: Unf Shelf Life: N/a
180000 pounds per square inch Countersink Angle: 100.0 degrees Screw Material: Steel comp 4140 or steel comp 4340 or steel comp 8740 Screw Surface Treatment: Cadmium Thread Series Designator: Unf Shelf Life: N/a
180000 pounds per square inch Countersink Angle: 100.0 degrees Screw Material: Steel comp 4140 or steel comp 4340 or steel comp 8740 Screw Surface Treatment: Cadmium Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure:
180000 pounds per square inch Countersink Angle: 100.0 degrees Screw Material: Steel comp 4140 or steel comp 4340 or steel comp 8740 Screw Surface Treatment: Cadmium Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: Demilitarization: No
180000 pounds per square inch Countersink Angle: 100.0 degrees Screw Material: Steel comp 4140 or steel comp 4340 or steel comp 8740 Screw Surface Treatment: Cadmium Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: Demilitarization: