NSN 5305-00-764-7753

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-764-7753

Thread Class
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.870 inches and 1.000 inches
Fastener Length:
Between 0.970 inches and 1.000 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.735 inches and 0.750 inches
Head Height:
Between 0.492 inches and 0.500 inches
Hole Diameter:
Between 0.061 inches and 0.067 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.500 inches
Width Across Flats:
Between 0.375 inches and 0.379 inches
Hole Quantity:
6
Hole Type:
Drilled There also Que Borde also (to i)
Thready Qty Per Inch (tpi):
20 Min Tanaila Strangth (nai)
Min. Tensile Strength (psi):
180000 pounds per square inch
Hardness Rating: 38.0 rockwell c and 45.0 rockwell c
Minimum Yield Strength:
155000 pounds per square inch
Hole Configuration Style:
Round longitudinal hole
Material:
Steel
Surface Treatment: Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 ty2 cl 2 federal specification single treatment response

NSN 5305-00-764-7753

Socket Head Cap Screw - Page 2 of 2



Thread Series Designator:
Unrf
Specification Data:
80205-nas1351 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0