

View Online at <https://aerobasegroup.com/nsn/5305-00-764-8900>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.125 inches and 0.135 inches

**Fastener Length:**

Between 0.240 inches and 0.250 inches

**Head Style:**

Headless (setscrew)

**Point Style:**

Flat

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.125 inches

**Thready Qty Per Inch (tpi):**

44

**Material:**

Steel comp 301 or steel comp 302 or steel comp 303 or steel comp 303f or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 323 or steel comp 324 or steel comp 347 or steel comp 348 or steel comp 385

**Material Specification:**

66 federal standard all material responses

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

171, finish no. 5.4.1 military standard single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0