NSN 5305-00-765-4348

Machine Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-765-4348 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.938 inches and 1.000 inches **Fastener Length:** 1.000 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.244 inches and 0.279 inches **Internal Drive Style:** Cross recess type 1 **End Application:** Helicopter, advance attack, ah-1w; consolidated targets; communications terminal, satellite an/gsc-3 (v) 1; aircraft, (ac-130h, mc-130h, ec-130e, hc **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 80000 pounds per square inch **Countersink Angle:** Between 80.0 degrees and 82.0 degrees **Screw Material:** Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Screw Material Specification:** 66 federal standard all material responses **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

Fiig: A500d0

No

Demilitarization: