Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-769-5612



Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 1.135 inches and 1.235 inches Fastener Length: Between 1.235 inches and 1.281 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.642 inches and 0.656 inches **Head Height:** Between 0.430 inches and 0.437 inches Locking Feature: Patch threads or pellet threads or strip threads **Internal Drive Style:** Hexagon **Thread Diameter:** 0.437 inches Width Across Flats: Between 0.375 inches and 0.379 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 45.0 rockwell c **Minimum Yield Strength:** 130000 pounds per square inch Material: Steel **Material Specification:** 66 federal standard single material response Surface Treatment: Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, class 3 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a

NSN 5305-00-769-5612

Socket Head Cap Screw - Page 2 of 2

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

