NSN 5305-00-772-1304

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-772-1304 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.265 inches **Fastener Length:** 2.656 inches **Head Style:** Flat chamfer **Head Diameter:** 0.234 inches **Head Height:** 0.500 inches **First Diameter From Head:** 0.125 inches **Second Diameter From Head:** 0.234 inches **Third Diameter From Head:** 0.144 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 2.187 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 2.250 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 2.391 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 3 Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate**

Unc

Thread Series Designator:

NSN 5305-00-772-1304

Externally Relieved Body Screw - Page 2 of 2



| Shelf Life: | She | lf | Life: |
|-------------|-----|----|-------|
|-------------|-----|----|-------|

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0