

View Online at <https://aerobasegroup.com/nsn/5305-00-772-1312>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.411 inches and 0.426 inches

Fastener Length:

3.166 inches

Head Style:

Flat chamfer

Head Diameter:

0.234 inches

Head Height:

Between 0.365 inches and 0.405 inches

First Diameter From Head:

0.156 inches

Second Diameter From Head:

0.116 inches

Third Diameter From Head:

0.234 inches

Fourth Diameter From Head:

Between 0.099 inches and 0.119 inches

Fifth Diameter From Head:

0.234 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

0.097 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

0.125 inches

Distance From Largest Bearing Surface Of Head To End Of Third Diameter:

0.171 inches

Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:

Between 2.678 inches and 2.693 inches

Distance From Largest Bearing Surface Of Head To End Of Fifth Diameter:

Between 2.740 inches and 2.755 inches

Internal Drive Style:

Slot

Thread Diameter:

0.164 inches

Thready Qty Per Inch (tpi):

32

Externally Relieved Body Diameter Quantity:

5

Material:

Steel comp 303

Material Specification:

Astm a582 assn standard single material response

Surface Treatment:

Passivate

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0