

View Online at <https://aerobasegroup.com/nsn/5305-00-772-2608>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.495 inches and 0.572 inches

**Fastener Length:**

Between 0.557 inches and 0.572 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.259 inches and 0.264 inches

**Head Height:**

Between 0.105 inches and 0.110 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.164 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

80000 pounds per square inch

**Screw Material:**

Steel comp 302 or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 309 or steel comp 310 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 322 or steel comp 324 or steel comp 347 or steel comp 303cu or steel comp 302b or steel comp 303ma or steel comp 303 or steel comp 303 plus x or steel comp 303se or steel comp 384

**Screw Surface Treatment:**

Passivate

**Screw Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unc

**Specification Or Standard:**

1 type and 4s style

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A500d0