
## NSN 5305-00-774-9453

Thumbscrew - Page 1 of 2





## **Thread Class:** 2a **Thread Direction: Right-hand Thread Length:** Between 0.391 inches and 0.422 inches Fastener Length: Between 0.688 inches and 0.719 inches **Head Style:** Knurled no. 1 **Head Diameter:** Between 0.734 inches and 0.766 inches **Head Height:** Between 0.234 inches and 0.266 inches **Shoulder Diameter:** 0.422 inches first shoulder and 0.453 inches first shoulder Shoulder Length: 0.109 inches first shoulder and 0.141 inches first shoulder **Point Style:** Cone **Thread Diameter:** 0.216 inches Thready Qty Per Inch (tpi): 24 Shoulder Shape: Round first shoulder **Special Features:** Thd relieved groove 0.062 in. W Material: Steel comp 303 Material Specification: Qq-s-764 federal specification single material response Surface Treatment: Passivate Surface Treatment Specification: Mil-f-14072, finish e300 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a Unit Of Measure:

---

## NSN 5305-00-774-9453

Thumbscrew - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.

