

View Online at <https://aerobasegroup.com/nsn/5305-00-775-5004>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.220 inches

**Fastener Length:**

3.485 inches

**First Diameter From Head:**

0.190 inches

**Second Diameter From Head:**

Between 0.250 inches and 0.260 inches

**Third Diameter From Head:**

Between 0.131 inches and 0.141 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.115 inches and 3.125 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

Between 3.165 inches and 3.175 inches

**Distance From Largest Bearing Surface Of Head To End Of Third Diameter:**

Between 3.235 inches and 3.265 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Material:**

Steel comp 302 or steel comp 316

**Material Specification:**

Mil-s-7720 military specification 1st material response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-7720 spec.